




E46 Wheel & Tyre Sets

Converting a car to accept larger wheels and tyres is not as simple as some would have you believe. Substantial consideration needs to be made to all of the dynamic effects of the wheels and tyres in conjunction with the chassis. In many cases the wheel arch apertures have to be widened to accept the biggest options, whilst moderate conversions may require little or no modification.

For these reasons, Hartge only supply wheels with compatible tyres as a set. Therefore you can be assured that each conversion will suit the dynamics of your car and any body modifications required have been meticulously tested and documented on each chassis. Where sets offered do require body modification, we always recommend that installation is carried out at our workshops. This may seem inconvenient, but our guarantee provides that there will be no body interference even when the vehicle is loaded to the maximum limit.

Hartge Classic		Hartge Classic and Classic II		
		Part No.	Description	Dimensions
		37 460 225	17" Classic Wheel & Tyre Set	8.5x17 with 225/45
		37 360 385	18" Classic Wheel & Tyre Set	8.5x18 with 225/40
		37 360 386	18" Classic Wheel & Tyre Set	8.5x18 with 225/40 & 255/35
		37 460 380	19" Classic Wheel & Tyre Set	8.0 & 9.0x19 with 235/35
		37 460 390	19" Classic Wheel & Tyre Set	8.0 & 9.0x19 with 235/35 & 265/30
Hartge Classic II		37 460 396	19" Classic Wheel & Tyre Set	9.0x19 with 255/30
		37 460 394	M3, 19" Classic Wheel & Tyre Set	9.0&9.5x19 with 245/35 & 275/30
		37 460 430	M3, 20" Classic Wheel & Tyre Set	9.0 & 10x20 with 245/30 & 285/25
		37 36 2385	Not M3, 18" Classic 2 Wheel and Tyre Set	8.5x18 with 225/40
		37 362 386	Not M3, 18" Classic Wheel and Tyre Set	8.5x18 with 225/40 & 255/35
		37 462 380	Not M3, 19" Classic 2 Wheel & Tyre Set	8.0 & 9.0x19 with 235/35
		37 462 390	Not M3, 19" Classic 2 Wheel & Tyre Set	8.0 & 9.0x19 with 235/35 & 265/30
		37 462 394	M3, 19" Classic 2 Wheel & Tyre Set	9.0&9.5x19 with 245/35 & 275/30
		37 462 430	M3, 20" Classic 2 Wheel and Tyre Set	9.0&10x20 with 245/30 & 285/25

Nova 3		Part No.	Front	Rear	Technical Requirements
		37 360 485	8.5 x 18" 225/40 Pirelli P7000	8.5 x 18" 225/40 Pirelli P7000	1
		37 360 486	8.5 x 18" 225/40 Pirelli P7000	8.5 x 18" 255/35 Pirelli P7000	2,3,4,5



To the right is a picture of a 3 series E46 saloon equipped with Hartge 19" Classic wheels. This car is also equipped with Hartge suspension and body kit.



Technical Requirements Key

1 Rear wheel arches may require flanges to be turned back.	6 Fitting kit required.
2 Rework the plastic rear wheel arch liner.	7 Steering rack limiter required.
3 Turn back the rear wheel arch flanges.	8 Rework the front wheel arch inner flitch panel.
4 Rework the bumper panel at the rear wheel arch.	9 Ensure 5mm clearance between tyre and front strut.
5 Rework the rear wheel arch inner flitch panel	10 Substantial expert modifications required at Birds workshop only.